



## 3232SE<sup>AC</sup> Electric Slim Scissor Lift

- Drives at Full Height Indoors Saving Time and Battery Energy Between Overhead Tasks
- Greater Productivity and Lower Cost of Ownership with Outrigger-Free Design
- AC Electric Drive for Extended Duty Cycles, Smoother Controls and Faster Drive Speeds
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- Maintenance-Free AGM Batteries



Do More Work by Driving Elevated Between Overhead Tasks up to 38 ft.

## Standard Features

### Work Area

Roll-Out Deck Extension with Incremental Locking Positions  
 Standard Swing Gate  
 Lanyard Attachments (4)

### Performance

Drive at Full Height Indoors  
 No Outriggers  
 AC Electric Drive  
 Fully Proportional Drive and Lift Controls  
 Up to 25% Gradeability

### Power

Maintenance-Free AGM Batteries  
 Battery Charge Indicator

### Serviceability

Lubrication-Free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical Components in a Slide-Out Tray  
 Logically Grouped Components and Numbered Wiring for Easy Reference

### Safety

Dedicated Compartment Protects Electrical and Hydraulic Components  
 Emergency Shut-Off at Platform and Lower Controls  
 Non-Skid Metal Deck Construction  
 Descent Alarm  
 Drive Speed Interlock  
 Multi-Axis Tilt Sensor  
 Scissor Maintenance Lock  
 Multiple Disc Brakes

### Other Features

|  |                              |
|--|------------------------------|
| Removable Upper Controls                             | Machine Tie Downs            |
| Voltage-Compensating Fully Automatic Battery Charger | Non-Marking Tires            |
| Fold-Down Guardrails                                 | All Motion Alarm             |
| Hour Meter   | Fork Lift Pocket             |
|  | Flashing Beacon (Continuous) |

## Optional Features

|   |   |
|---|---|
| Leak Containment System® (LCS)<br><i>Patent #11,112,060</i> | Proactive Platform Safety System® (PPSS)        |
| 900W Inverter   | Upper Control Box Supplementary Guard Pipe Rack |
| Tool Tray   | Second Year Extended Warranty                   |
| Cold Weather Package  |   |



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com

MEC®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent #11,112,060.

97043 DTD 1023

| 3232SE <sup>AG</sup>           | U.S.                                 | Metric     |
|--------------------------------|--------------------------------------|------------|
| <b>Heights</b>                 |                                      |            |
| Indoor Working Height*         | 38 ft.*                              | 11.6 m*    |
| Outdoor Working Height*        | 30 ft.*                              | 9.1 m*     |
| Indoor Platform Height         | 32 ft.                               | 9.8 m      |
| Outdoor Platform Height        | 24 ft.                               | 7.3 m      |
| Stowed Height (Top Guardrail)  | 96 in.                               | 2.4 m      |
| Stowed Height (Rails Folded)   | 78 in.                               | 2 m        |
| Stowed Height (Platform Floor) | 53 in.                               | 1.3 m      |
| Guardrail Height               | 43.5 in.                             | 1.1 m      |
| Toeboard Height                | 6 in.                                | 15 cm      |
| Ground Clearance (Stowed)      | 4 in.                                | 10 cm      |
| Ground Clearance (Elevated)    | 0.7 in.                              | 1.8 cm     |
| <b>Dimensions</b>              |                                      |            |
| Length-Stowed (Overall)        | 97 in.                               | 2.5 m      |
| Length-Stowed (Ladder Removed) | 89.5 in.                             | 2.3 m      |
| Chassis Width                  | 32 in.                               | 81 cm      |
| Platform Length (Extended)     | 124.5 in.                            | 3.2 m      |
| Platform Length (Retracted)    | 89.5 in.                             | 2.3 m      |
| Roll-Out Deck Length           | 35 in.                               | 90 cm      |
| Platform Width                 | 29 in.                               | 74 cm      |
| Wheelbase                      | 74 in.                               | 1.9 m      |
| Total Lift Capacity            | 550 lbs                              | 250 kg     |
| Personnel Capacity             | 2 (Indoors); 1 (Outdoors)            |            |
| Roll-Out Deck Capacity         | 250 lbs                              | 113 kg     |
| <b>Speed</b>                   |                                      |            |
| Raise/Lower Speed              | 52 s / 38 s                          |            |
| Drive Speed (Stowed)           | 3 mph                                | 5 km/h     |
| Drive Speed (Elevated)         | 0.5 mph                              | 0.8 km/h   |
| <b>Performance</b>             |                                      |            |
| Gradeability                   | 25%                                  |            |
| Turning Radius (Inside)        | 0 in.                                | 0 m        |
| Weight**                       | 7,145 lbs.                           | 3240 kg    |
| Power Source                   | 24v 240Ah Maintenance-Free Batteries |            |
| Controls                       | Proportional Drive & Lift Controls   |            |
| Tires                          | 15 x 5 in.                           | 38 x 13 cm |

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.  
 \*\*Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6 - 2017.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: